

[Products](#) > [By Parameter](#) > [pH](#)

## CyberScan pH 300


[VIEW ENLARGED IMAGE](#)


### Product Features

- ⌘ Waterproof and Dustproof Housing - IP67 rated, ideal for rugged harsh conditions. Plus it floats!
- ⌘ Multi-Point Push-button Calibration (up to 5/6 points) with Auto-Buffer Recognition - choice of USA, NIST or DIN buffer standards for quick calibration with no calibration mistakes
- ⌘ User-Customization for enhanced flexibility and viewing of electrode diagnosis - pH slope/offset/mV base value, previous calibration points
- ⌘ Built-in Real-time Clock stamps stored data and calibration data with time & date - meets standards for GLP purposes (available in pH310)
- ⌘ Expanded memory stores and recalls up to 50 readings with temperature (available in pH310)
- ⌘ Automatic Temperature Compensation (ATC) for the highest accuracy under fluctuating temperatures
- ⌘ Stability Indicator prompts whenever reading stabilizes
- ⌘ Auto-Hold Function automatically freezes reading when stabilized for easy viewing and recording
- ⌘ Auto-Power Off conserves battery power and save money
- ⌘ Self-Diagnostic with message codes for easy troubleshooting
- ⌘ Large, Easy-to-Read Custom LCD Display with simultaneous readings provides optimum viewing with user-friendly icons
- ⌘ Rugged Carrying Case (Optional) provides handy on-site meter calibration and measurement



Ergonomic design



Carrying kit set



Adjustable probe holder

### Search Our Site



### Product Search



### Related Information

[Worldwide Offices](#)
[Online Enquiry](#)

### Applications

**Industrial:** Ideal for checks in water conditioning plants, cooling towers, plating and finishing operations, food processing (for HACCP compliance), water testing, printing and chemical industries, rinse water analysis, water/wastewater treatment and chemical process verification. Use with ORP electrode to monitor plating operations, and other redox measurements.

**Environmental/Agricultural:** Use in ecology studies, aquariums, and hydroponics.

**Laboratory/Educational:** Use in all types of food analysis, quality assurance testing, any laboratory where GLP management is required, petrochemical, chemical applications.

### Specifications

Product Specification	Description
<b>pH Range</b>	-2.00 to 16.00 pH
<b>Resolution &amp; Accuracy</b>	0.01 pH & ± 0.01 pH
<b>mV Range</b>	±199.9 mV (extended); ±1999 mV
<b>Resolution &amp; Accuracy</b>	0.1 mV & ±0.2 mV (within 199.9 mV); 1 mV & ±2 mV (beyond ±200 mV)
<b>Temperature Range</b>	0 to 100.0 °C
<b>Resolution &amp; Accuracy</b>	0.1 °C & ± 0.3 °C
<b>No. of Calibration Points</b>	1 to 5
<b>pH Buffer Options</b>	USA: 1.68, 4.01, 7.00, 10.01, 12.45
<b>Memory</b>	16 sets
<b>Temperature Compensation</b>	Automatic / Manual (0 to 100 °C)
<b>Date/Time Stamping</b>	No
<b>Special Functions</b>	Auto-Hold; Auto Power-Off after 30 minutes; Stability Indicator, Self-diagnostics messages
<b>Power</b>	4 'AAA' x 1.4V batteries

### Order Information

Order No.	Item
<b>EC-PHWP300/02K</b>	Waterproof CyberScan pH 300 Portable pH Meter with pH electrode, temperature probe, 2 electrode holders and CyberScan pH carry kit set (EC-PHWP-KIT)
<b>EC-PHWP-KIT</b>	CyberScan pH Carry Kit Set – CyberScan Plastic Carry Case comprises 1 x pH 4.01, pH 7.00, pH 10.01 buffer solutions (60 ml each) and 1 x empty rinse water bottle

[Sales Enquiry](#)  
[Service Enquiry](#)
[Products](#) > [By Parameter](#) > [pH](#)